



/// Click on above images to enlarge

### BOOM Specs

Boom Specifications	U.S.	Metric
Pipeline Diameter	5"	125 mm
Vertical reach	106'	32 m
Reach From Slewing Axis	93'	28.3 m
Net Horizontal reach	84' - 4"	25.7 m
Unfolding Height	25' - 4"	7.5 m
<b>Section Lengths:</b>		
First Section	25' - 11"	7.9 m
Second Section	23' - 1"	7 m
Third Section	23' - 1"	7 m
Fourth Section	20' - 10"	6.3 m
Slewing Range	400 deg.	400 deg.
End hose Length	12' - 6"	3.8 m

Specifications are subject to change without prior notice.

### PUMP Specs

Pump Kits	32 XG: 2023-4 125/80 SC	32 XL: 2025-5 120/80 MPS	32XL: (Detach Only) 2023-5 130/80 MPS
Theor. Concrete Output (cu.yds/hr)	170	178	208
Max. Pressure on Concrete (psi)	1285	1233	1007
Max. Strokes/Min.	26	23	32
Pump Cylinder Diameter (in.)	9	10	9
Pump Cylinder Stroke Length (in.)	79	79	79
Differential Cylinder Size (in.)	4.9	4.7	5.1
Max. Aggregate size (in.)	2.5	2.5	2.5

Specifications are subject to change without prior notice.

### Options

/// Click above for KVM 32 XL/XG accessories & options